

**NEW
Materials
Available**

Rubber Fab Technologies Group's

GAUGE PROTECTION SYSTEM

Assures Protection of
Instrumentation with
No Product Loss



**Available
Materials Include:**

- Platinum Silicone
- PTFE **NEW!**
- Tuf-Steel **NEW!**
- FKM
- EPDM

RUBBER FAB
technologies group

The Rubber Fab Gauge Guard Isolator seals **protect expensive stainless steel diaphragms and instruments from damage without affecting instrument performance.** By combining a quality Rubber Fab hygienic seal with a membrane, the Gauge Guard Isolator hygienic seal **isolates corrosive solutions from the stainless steel diaphragm.** A necessary and **cost effective** step in **assuring long life and accurate results from your gauges.**

As some manufacturers will suggest the use of a gauge guard seal, others note that the **failure to use a gauge guard seal can void most instrument and gauge warranties.**

All the Rubber Fab Benefits in a Gauge Guard Hygienic Seal

- Seal membrane **protects stainless steel diaphragm from corrosive solutions**
- **Will not interfere with gauge operation or accuracy**
- Works with most industry standard instruments
- Helps **extend the life** of gauges
- Available in:
Platinum Silicone
PTFE
Tuf-Steel®
EPDM
FKM Fluoroelastomer

- 1/2" and 3/4" – .015 membrane thickness
- 1", 1-1/2" and 2" – .010 membrane thickness

All Rubber Fab Hygienic Seals Meet the Stringent Standards For Purity

- U.S. Pharmacopeia Class VI Certification
- Cytotoxicity Criteria
- Title 21 CFR 177.2600
- USDA and 3-A Sanitary Standards
- Current Good Manufacturing Practices (CGMP)
- ASME-BPE Standards
- Animal Derived Ingredient Free

© ADI Free is a registered trademark of Rubber Fab Technologies Group



RUBBER FAB
technologies group

26 Brookfield Drive • Sparta, NJ 07871
 973.579.2959 • Toll Free: 866.442.2959
 Fax: 973.579.7275 • sales@rubberfab.com

www.rubberfab.com



EPDM

1/2"	42GGI-E-050
3/4"	42GGI-E-075
1"	40GGI-E-100
1-1/2"	40GGI-E-150
2"	40GGI-E-200

Temperature: Up to 250°F



Platinum Silicone

1/2"	42GGI-PX-050
3/4"	42GGI-PX-075
1"	40GGI-PX-100
1-1/2"	40GGI-PX-150
2"	40GGI-PX-200

Temperature: Up to 300°F



FKM Fluoroelastomer

1/2"	42GGI-SFY-050
3/4"	42GGI-SFY-075
1"	40GGI-SFY-100
1-1/2"	40GGI-SFY-150
2"	40GGI-SFY-200

Temperature: Up to 400°F



PTFE

1"	40GGI-G-100
1-1/2"	40GGI-G-150
2"	40GGI-G-200

Temperature: Up to 450°F



Tuf-Steel®

1"	40GGI-TS-100
1-1/2"	40GGI-TS-150
2"	40GGI-TS-200

Temperature: Up to 500°F

Rubber Fab Technologies Group is a member of:

Distributed by:



Email info@puretransfer.com
www.puretransfer.com
 Tel: 033 39 390 034